

MODEL	DESCRIPTION	LIST PRICE
-------	-------------	------------

**BG-3000**  
**Water Filtration**  
**System**

Part # WI-BG3000

Shipping Wt: 5 lbs.

\$ 759

Shipping Wt: 30 lbs.

6-PK Ea. \$ 729

12-PK Ea. \$ 701


**LEVEL 2 Body Glove Water Filter System.**

Featuring Tri Stage filtration and advanced protection from particles 0.5 micron in size and larger.

A filter change indicator is included.

 RECYCLE KIT AVAILABLE FOR \$20 AT [WATERINC.COM/RECYCLE](http://WATERINC.COM/RECYCLE)
**FLOW RATE:** 0.75 GPM

**CAPACITY:** 450 gallons or 1 year

**Dimensions:** W = 4.5" / D = 4.75" / H = 15.75"

(height includes 2.5" clearance for cartridge change purposes)

For filter faucet options, see our faucet guides: pages 42 &amp; 43.

Enhance your water with an EverHot® Instant Hot System or EverCold® Water Chiller.

**REDUCES:** Chlorine Taste & Odor • Chloramines • \*Cloudiness, Sediment, Rust

\*Giardia Lamblia Cysts • \*\*Cryptosporidium Parvum Cysts • Lime Scale

Asbestos Fibers • \*Oxidized Iron • \*Oxidized Manganese • \*Oxidized Sulfides

Lead • 0.5-1.0 Micron, Nominal Particulate Reduction, Class 1

Volatile Organic Chemicals (VOCs)

\*Based on Manufacturer's Data \*\*Tested using Live Cyst as a surrogate


 System Tested and Certified  
 by NSF International  
 against NSF/ANSI Standards  
 42, 53 and CSA B48 3.1 in Model  
 BG-3000 for the reduction of:

**Standard 42 - Aesthetic Effects**

- Chemical Reduction
- Chlorine Taste & Odor
- Chloramines
- Mechanical Filtration
- Particulate Reduction- Class I

**Standard 53 - Health Effects**

- Chemical Reduction
- Lead • VOC
- Mechanical Filtration
- Cysts • Asbestos

**BG-3000C**  
**Replacement**  
**Cartridge**

Part # WI-BG3000C

Shipping Wt: 3 lbs.

Ea. \$ 326

Shipping Wt: 15 lbs.

6-PK Ea. \$ 313

12-PK Ea. \$ 302

**FLOW RATE:** 0.75 GPM / **CAPACITY:** 450 gallons or 1 year

**EASY QUICK-CHANGE REPLACEMENT CARTRIDGE:** Body Glove Water Filter Systems have an automatic shut-off valve built into the head unit, so changing the cartridge is a breeze. Includes a filter change indicator.


Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.


**MAXIMUM recommended line pressure for this product is 75 PSI.** Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, **confirm that water supply pressure does not exceed 75 PSI.** Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)

Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.