



MODEL	DESCRIPTION	LIST PRICE
-------	-------------	------------

BG-1000 Water Filtration System

Part # WI-BG1000

Shipping Wt: 4 lbs.

\$ 663

Shipping Wt: 24 lbs.

6-PK Ea. \$ 637

12-PK Ea. \$ 612



LEVEL 1 Body Glove Water Filter System.

Featuring Tri Stage filtration and advanced protection from particles 0.5 micron in size and larger.

A filter change indicator included.

RECYCLE KIT AVAILABLE FOR \$20 AT WATERINC.COM/RECYCLE

FLOW RATE: 0.75 GPM

CAPACITY: 1,000 gallons or 1 year

Dimensions: W = 4.5" / D = 4.75" / H = 18"

(height includes 2.5" clearance for cartridge change purposes)

For filter faucet options, see our faucet guides: pages 42 & 43.

Enhance your water with an EverHot® Instant Hot System or EverCold® Water Chiller.

**MOST
ECONOMICAL
MODEL!**
with
lead reduction

REDUCES:

Chlorine Taste & Odor • *Cloudiness, Sediment, Rust • **Giardia Lamblia Cysts
**Cryptosporidium Parvum Cysts • Lime Scale • Asbestos Fibers
*Oxidized Iron • *Oxidized Manganese • *Oxidized Sulfides
Lead • 0.5-1.0 Micron, Nominal Particulate Reduction, Class 1

*Based on Manufacturer's Data **Tested using Live Cyst as a surrogate



System Tested and Certified
by NSF International
against NSF/ANSI Standards 42 and 53
in Model BG-1000 for the reduction of:

Standard 42 - Aesthetic Effects

- Chemical Reduction
- Chlorine Taste & Odor
- Mechanical Filtration
- Particulate Reduction- Class I

Standard 53 - Health Effects

- Chemical Reduction
- Lead
- Mechanical Filtration
- Cysts • Asbestos

BG-1000C Replacement Cartridge

Part # WI-BG1000C

Shipping Wt: 2 lbs.

Ea. \$ 262

Shipping Wt: 10 lbs.

6-PK Ea. \$ 253

12-PK Ea. \$ 243



FLOW RATE: 0.75 GPM / **CAPACITY:** 1,000 gallons or 1 year

EASY QUICK-CHANGE REPLACEMENT CARTRIDGE: Body Glove Water Filter Systems have an automatic shut-off valve built into the head unit, so changing the cartridge is a breeze. Includes a filter change indicator.



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)

Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.