

REVERSE OSMOSIS



MODEL DESCRIPTION LIST PRICE

HousePure® **RO-3000 Reverse Osmosis Drinking Water** System

PART # WI-HP-RO-3000

Shipping Wt: 25 lbs.

\$1,206

Replacement Cartridges


PART # WI-HP-RO-3000-FILTERKIT

To be replaced annually

\$324 \$610

PART # WI-HP-RO-3000-MEMBRANE

To be checked annually and replaced per its performance, 5 years maximum



4-cartrigde housing, storage tank & Chrome Air Gap Faucet PLUS a TDS meter to check your membrane's performance annually

CARTRIDGE HOUSING DIMENSIONS: 12.54" H / 14.57" W / 5.46" D

STORAGE TANK DIMENSIONS 14.61" H / 10.91" Diameter



System Tested and Certified by NSF International against NSF/ANSI Standard 42, 53, 58, and CSA B483.1 for the reduction of the claims specified on the Performance Data Sheet.

The finest in Reverse Osmosis is the HP-RO-3000. This system provides 21 gallons of truly purified water per day for you and your family. Designed to remove many impurities from your water, this system is the perfect choice for homes with salt-using water softeners, regions with specific water concerns like arsenic, and people who wish to reduce fluoride.

Substance	Influent Challenge Concentration	Max. Permissible Product Water Concentration	Reduction Requirements	Average Reduction
STANDARD 42				
Chlorine Taste & Odor	2.0 mg/L ± 10%		>50%	95.9%
STANDARD 53				
Cysts*	Minimum 50,000/L		99.95%	99.99%
Atrazine	0.009 mg/L ± 10%	0.003 mg/L		93.7%
Lead (pH 6.5)	0.15 mg/L ± 10%	0.010 mg/L		99.9%
Lead (pH 8.5)	0.15 mg/L ± 10%	0.010 mg/L		99.6%
Lindane	0.002 mg/L ± 10%	0.0002 mg/L		97.4%
STANDARD 58				
Total Dissolved Solids	750 ± 40 mg/L	187 mg/L		96.3%
Pentavalent Arsenic	0.050 mg/L ± 10%	0.010 mg/L		88.0%
Fluoride	8.0 mg/L ± 10%	1.5 mg/L		93.6%
Cysts*	Minimum 50,000/mL		99.95%	99.99%
Turbidity	11 mg/L ± 1 NTU	0.5 NTU		>99.1%
Lead	0.15 mg/L ± 10%	0.010 mg/L		98.6%
Selenium	0.10 mg/L ± 10%	0.05 mg/L		97.9%
Copper	3.0 mg/L ± 10%	1.3 mg/L		98.5%
Cadmium	0.03 mg/L ± 10%	0.005 mg/L		99.1%
Hexavalant Chromium	0.3 mg/L ± 10%	0.1 mg/L		96.4%
Trivalent Chromium	0.3 mg/L ± 10%	0.1 mg/L		98.2%
Radium 226/228	25 pCi/L ± 10%	5 pCi/L		80.0%
Barlum	10.0 mg/L ± 10%	2.0 mg/L		96.3%

- NSF certified for peace of mind (NSF Standard 42, 58 and 53).
- Effortless with click-in lock cartridge installation.
- Color coded cartridges maintains proper filter sequence.
- Chrome air gap faucet included.
- TDS meter included to check your membrane performance.
- Upgrade products: we have decorative RO faucets and a multipurpose air gap that are available in many finishes.
- Add alkaline improvement with our post filter (see page 19).

PRESSURE RANGE = 40-75 PSI

RECOVERY RATING = 41.05%

EFFICIENCY RATING = 23.57%

TDS REJECTION = 96.3% (average for new membrane cartridge)


PRODUCTION = 21.08 GALLONS PER DAY (@ 75 PSI)

FOR ALL OUR REVERSE OSMOSIS SYSTEM ACCESSORIES FOR ALL OUR

Upgraded Filter Faucets and EverHot Instant Hot

MANY STYLES AND FINISHES see page 42 for our faucet guide

AIRGAP: Wall Mounted. PART# WI-RO-WALL-AIRGAP LIST PRICE \$43 see page 76



Looking for 3M Reverse Osmosis? We are a proud master distributor of 3M Residential and 3M Commercial Products



Scan this QR code receive 3M Pricing