

MODEL	DESCRIPTION	LIST PRICE
-------	-------------	------------

.75"
HousePure® Secure
Tankless Water
Heater Protection

Part # WI-HP-SECURE-.75L (water entry left side)
Part # WI-HP-SECURE-.75R (water entry right side)

Shipping Wt: 7 lbs. Ea. \$ 397
6-PK Ea. \$ 382
12-PK Ea. \$ 377

Utilizes Siliphos Polyphosphate
Recommended for all Tankless Water Heater Manufacturers



LEVEL 1 Tankless Water Heater Scale Prevention.

Provides annual protection against costly water heater scaling and sediment build-up. Polyphosphate media prevents (sequesters) water hardness from scaling on flash heating surfaces. A 5-micron filter reduces sediment, which can cause additional scaling throughout the hot water line. The unique micro-fiber filter construction delivers higher filtration efficiency and flow rates. Ideal for indoor and outdoor installations (not for below freezing temperatures). Features a 3/4" NPT inlet/outlet with a differential filter-change gauge for peace-of-mind.

Includes mounting bracket, filter-change indicator gauge, filter-change spanner wrench, and a Water, Inc. annual filter change indicator.

Max Flow Rate: 9 GPM

Dimensions: Width: 5.25" Height: 25.75" Depth: 5.5"

Filter Capacity: One year or when gauge or timer indicates change needed

Incoming Water Temperature Range: 40°F to 100°F

Tools Required: Teflon® tape (do **not** use pipe dope), adjustable wrench, tube cutter, suitable pipe fittings and inlet gate valve



[annual filter change indicator]



Component Tested to NSF/ANSI Standard 42
for material requirements.

YOU CHOOSE!
RIGHT or LEFT
water entry side

HousePure® Secure
Replacement
Cartridge

Part # WI-HP-SECURE-.75C

Shipping Wt: 1 lbs.

Ea. \$ 87

Shipping Wt: 19 lbs.

6-PK Ea. \$ 84

12-PK Ea. \$ 81



The HousePure Secure cartridge should be changed annually or when gauge indicates a change is needed sooner.

Utilizes Siliphos Polyphosphate

Capacity: One year or when gauge indicates change needed

Dimensions: Height: 20" Diameter: 2.5"

Included: replacement lubricated o-ring & filter change indicator.

Replacement Cartridge for HousePure® Secure 3/4" tankless water heater filter system. The 5-micron filter with polyphosphate scale reducing media provides consistent flow rates and superior filtration performance.

Recommended for all Tankless Water Heater Manufacturers

Tested to NSF/ANSI Standard 42 for material requirements.



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, **confirm that water supply pressure does not exceed 75 PSI.** Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)