

MODEL	DESCRIPTION	LIST PRICE
-------	-------------	------------

1.5"
HousePure® Secure
Tankless Water
Heater Protection

Part # WI-HP-SECURE-1.50L (water entry left side)
Part # WI-HP-SECURE-1.50R (water entry right side)

Shipping Wt: 19 lbs. Ea. \$ 487
6-PK Ea. \$ 459
12-PK Ea. \$ 441

Utilizes Siliphos Polyphosphate
Recommended for all Tankless Water Heater Manufacturers



LEVEL 2 High Flow Tankless Water Heater Scale Prevention.

Provides annual protection against costly water heater scaling and sediment build-up. Polyphosphate media prevents (sequesters) water hardness from scaling on flash heating surfaces. A dual-gradient 50 over 5 micron filter reduces sediment, which can cause additional scaling throughout the hot water line. The gradient density filter design provides up to three times the dirt-holding capacity of similar size sediment cartridges. The unique micro-fiber filter construction delivers higher filtration efficiency and flow rates. Ideal for indoor and outdoor installations (not for below freezing temperatures). Features a 1-1/2" NPT inlet/outlet with a pressure-change gauge for peace-of-mind.

Includes powder-coated mounting bracket, indicator gauge, filter-change spanner wrench and a Water, Inc. annual filter change indicator


Max Flow Rate: 20 GPM

Dimensions: Width: 7.5" Height: 29" Depth: 8.75"

Filter Capacity: One year or when gauge indicates change needed

Incoming Water Temperature Range: 40°F to 100°F

Tools Required: Teflon® tape (do **not** use pipe dope), adjustable wrench, tube cutter, suitable pipe fittings, and inlet gate valve



[annual filter
change indicator]



Component Tested to NSF/ANSI Standard 42
for material requirements.

YOU CHOOSE!
RIGHT or LEFT
water entry side

HousePure® Secure Part # WI-HP-SECURE-1.50C
Replacement
Cartridge

Shipping Wt: 4 lbs. Ea. \$ 142
Shipping Wt: 23 lbs. 6-PK Ea. \$ 136
12-PK Ea. \$ 131



The HousePure Secure cartridge should be changed annually or when gauge indicates a change is needed sooner.

Utilizes Siliphos Polyphosphate

Capacity: One year or when gauge indicates change needed

Dimensions: Height: 20" Diameter: 4.5"

Included: replacement lubricated o-ring & filter change indicator.

Replacement Cartridge for HousePure® Secure 1.5" tankless water heater filter system. The dual-gradient 50 over 5 micron filter with polyphosphate scale reducing media provides consistent flow rates and superior filtration performance.

Recommended for all Tankless Water Heater Manufacturers

Tested to NSF/ANSI Standard 42 for material requirements.



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)