

MODEL	DESCRIPTION	LIST PRICE
-------	-------------	------------

HousePure® SS-2
Commercial Grade
Water Filter System
PLUS
ScaleStop
Conditioner Tank

Part # WI-HP-SS-2

Shipping Wt: 350 lbs.

\$ 11,590

CHLORAMINE UPGRADE

Part # WI-HP-SS-2-CHL

\$ 13,882

The HousePure ScaleStop 2 is a high capacity commercial whole home filter PLUS a ScaleStop Conditioner tank. The HPSS 2 boasts 2" inlet and outlet lines for larger homes and businesses that require higher flow rates with the added scale control capacity. The pretreatment tank offers 4 cubic feet of premium coconut shell granular activated carbon along with 10 lbs of KDF-55 media. Together, these two mediums create a high degree of pretreatment benefits including dechlorination, bacteria inhibition, and taste and odor reduction. The second tank contains 88% more ScaleStop media than residential systems, ensuring that all water is properly treated for scale control.

The HPSS-2 has a 2" inlet and outlet, which can be bushed down to accept smaller pipe sizes if needed. The unit includes a 2900 series commercial, 24VDC controller and a 2" metered valve.

Includes Installation Parts and Install/Owner's Manual

Dimensions (Including both tanks): Width: 34" Height: 80" Depth: 32"

Distance between tanks: 2"

Rough In Dimension: 67" and 55"

Flow Rate: 30 GPM

Pipe Size: 2" inlet and outlet*, 1" drain

Media: 4 cubic feet, coconut shell GAC (granular activated carbon) & 10 lbs, KDF-55
+ 7.5-liters, ScaleStop resin

CHL Upgrade Media: 4 cubic feet, surface modified GAC & 10 lbs, KDF-55
+ 7.5-liters, ScaleStop resin

Operating Temp Range: 34°F to 110°F (Not appropriate for freezing temperatures.)

Water Pressure Range: 20 PSI to 75 PSI

Operating Voltage: 24 VAC, 50/60 Hz, 120 VAC transformer included

Water Quality: Not for use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system



Component Tested to NSF/ANSI Standard 42
for material requirements.



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.



CUSTOMERS CONCERNED WITH CHLORAMINES CAN UPGRADE THIS PRODUCT.

Our catalytic enhanced GAC (Granular Activated Carbon) has been surface modified during manufacturing. Our product is 3 times more effective than competitive products and 15 times more effective than our standard HousePure media.

Upgrade to more complete chloramine reduction! WI-HPSS-2-CHL List Price \$ 13,882

ESSENTIAL SCALESTOP INFO - PLEASE READ

This is not a water softener. To assist you in your understanding of this product, you must read and sign the "ScaleStop Customer Expectation Form" (shown on page 31) before purchasing HousePure ScaleStop products. The customer's signed form must be provided with the dealer's purchase order. Thank you!

When installed in homes with new pipes, system MUST be in bypass mode for 120 days before use.

READ & SIGN



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, **confirm that water supply pressure does not exceed 75 PSI.** Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)