



TWIN TANK WHOLE HOUSE WATER SOFTENER

This twin tank system delivers maximum water quality from the first drop to the last.

Housepure 9100TS softeners have a proven platform of technology for guaranteed performance. Get the most from your system while conserving resources and saving money. Its advanced sensor adjusts to meet your home's changing demands. Equipped with two softening tanks so there is never a shortage of softening capacity. And a microprocessor-based controller works smarter to conserve water and save regenerant.

Component tested to NSF/ANSI Standard 42 for material requirements.



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.

HousePure® Whole House Twin Tank Water Softener

Model 9100TS844

HousePure® Whole House Twin Tank Water Softener

Model 9100TS1248

Part# WI-HP-9100TS844

List Price: \$ 5,661

Shipping Wt: 200 lbs.

Includes Installation Kit

Dimensions

Height: 51"

Depth: 20"

Width (across both tanks and brine tank): 44"

Distance between tanks: 4 1/2"

Brine Tank may be placed any distance from the tanks

Brine Tank: 11" x 11" x 34"

Rough In Dimension: 47"

FLOW RATE: 10 GPM

CONNECTION: 1" NPT provided

3/4" - 1 1/4" plumbing connection, other sizes available*

Threaded or sweat, plastic or brass connections available at an additional cost*

DRAIN: 1/2" pipe

MEDIA: 1 cubic foot, high-capacity cation resin

SALT CAPACITY: 225 lbs. (approx 4 bags)

* Optional installation connections are available, see page 38-39

Part# WI-HP-9100TS1248

List Price: \$ 7,092

Shipping Wt: 350 lbs.

Includes Installation Kit

Dimensions

Height: 55"

Depth: 30"

Width (across both tanks and brine tank): 44"

Distance between tanks: 2"

Brine Tank may be placed any distance from the tanks

Brine Tank: 15" x 15" x 35"

Rough In Dimension: 51"

FLOW RATE: 17 GPM

CONNECTION: 1" NPT provided

3/4" - 1 1/4" plumbing connection, other sizes available*

Threaded or sweat, plastic or brass connections available at an additional cost*

DRAIN: 1/2" pipe

MEDIA: 2 cubic feet, high-capacity cation resin

SALT CAPACITY: 225 lbs. (approx 4 bags)

* Optional installation connections are available, see page 38-39

Helpful water softener facts:

For the salt (brine) tank, you can use sodium chloride or potassium chloride. Note: if sodium chloride is used, the softened water cannot be used for watering gardens or for other irrigation uses.

*The installation of a **reverse osmosis drinking water system** is recommended for persons with heart disease hypertension, high blood pressure or a low sodium diet. See page 16-17 for reverse osmosis systems.*



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)