

MODEL	DESCRIPTION	LIST PRICE
-------	-------------	------------

HousePure SOFT
Whole House
Water Softeners

Part# WI-HP-SOFT-2

Shipping Wt: 185 lbs.

\$4,178

Part# WI-HP-SOFT-2-WIFI
WITH UPGRADED WIFI HEAD

Shipping Wt: 185 lbs.

\$5,153

Part# WI-HP-SOFT-3

Shipping Wt: 300 lbs.

\$4,710

Part# WI-HP-SOFT-3-WIFI
WITH UPGRADED WIFI HEAD

Shipping Wt: 300 lbs.

\$5,637



The HousePure high flow industrial water softener provides whole-house protection against costly water hardness scaling and lime scale build-up. Enjoy the gentle caress of softened water from every faucet, bath and shower. Extend the life of your home: softened water protects appliances, fixtures and plumbing lines. The HousePure Soft is an ideal solution for hard water spotting and scaling damage. Now with two models available, compare the Soft-2 and the Soft-3 below. Both are upgradable with a WiFi head.

An electronic water meter provides quick setup and programming, while an integrated battery backup offers peace-of-mind during power interruptions. The softener regenerates and self cleans on a regular basis. Ideal for indoor and outdoor installations. Includes Installation Parts and Install/Owner's Manual.



HP-SOFT-2

HP-SOFT-3

VALVE FLOW RATE	35 GPM	35 GPM
EFFECTIVE SYST. FLOW RATE	19 GPM	27 GPM
OVERALL DIMENSIONS (INCLUDING BRINE TANK)	W 34" / H 63" / D 20" (with bypass straight) or 18" (with bypass 90° up or down)	W 34" / H 77" / D 20" (with bypass straight, 90° up or down)
BRINE TANK	19" diameter (place any distance from tank)	19" diameter (place any distance from tank)
ROUGH IN DIMENSION	55"	69 1/4"
CONNECTION	1 1/2" inlet/outlet, 1/2" discharge outlet	1 1/4", 1 1/2" NPT plastic connectors (set)
SOFTENING CAPACITY	48,000 grains of hardness	72,000 grains of hardness
MEDIA	2 cubic feet, high capacity cation resin	3 cubic feet, high capacity cation resin
SALT CAPACITY	400 lbs.	700 lbs.

Operating Temperature Range: 34°F to 110°F (not appropriate for freezing temperatures)

Water Pressure Range: 20 PSI to 75 PSI

Operating Voltage: 24 VAC, 50/60 Hz, 120 VAC transformer included

Water Quality: Not for use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Component Tested to NSF/ANSI Standard 42
for material requirements.



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.

* Optional installation connections are available, see page 38-39

Helpful water softener facts:

For the salt (brine) tank, you can use sodium chloride or potassium chloride. Note: if sodium chloride is used, the softened water cannot be used for watering gardens or for other irrigation uses.

*The installation of a **reverse osmosis drinking water system** is recommended for persons with heart disease, hypertension, high blood pressure or a low sodium diet.
See page 16-17 for reverse osmosis systems.*



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)