

MODEL	DESCRIPTION	LIST PRICE
-------	-------------	------------

EVERCOLD

Part # WI-WIC500S

\$ 1,105



Shipping Weight: 36 lbs.

Improved undercounter instant chilled water unit hooks up to any of our EverHot dual faucets when used with EverHot unit. Requires a single accessory faucet when installed separately.

Construction of waterways is made of the highest quality lead free materials (304 stainless steel).

Equipped with leak detection and automatic water shut-off.
Improved ventilation elevates chiller performance.

Installation is quick and easy with 1/4" quick connect fittings.

Cooling: The refrigeration system is hermetically sealed to virtually eliminate refrigerant gas leakage. Contains HFC 134a refrigerant gas, which offers a zero ODP (Ozone Depletion Potential). The cooling unit is a maintenance-free compressor protected by automatic restarting motor cut-off. Condenser fan for improved performance. External tube evaporator.

Cabinet: 304 Brushed stainless steel. Supplied with 3' long flow insulation water supply tubing.

Electrical: 1.80 Amps, 110 Volts, 60 Hz, monophase, 140 Watts.
Includes 6' electrical cord with 3-prong plug.

Performance: 1.26 gallons (4.8 liters) per hour of 50° F drinking water, based on 90° F inlet water.

Capacity: Refrigeration tank has .6 gallon capacity (2.25 liters).

Dimensions: Width: 16"
Height: 11.5"
Depth: 8.5"

TAKE A LOOK AT OUR EVERCOLD® CHILLED & AMBIENT enhanced water package on page 71.



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CA AB 1953 and VT Act 193.



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)

Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.