



MODEL DESCRIPTION LIST PRICE

FLOW CONTROL MONITORS

Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.



Two AAA alkaline batteries are included.

Part # WI-BG-MONITOR-PRG (programmed in 100 gallon increments from 500 to 6,000 gallons)

Ship Wt: 1 lb.

\$86

DigiFlow Electronic Flow Meter

Includes Flow Meter, fittings, two AAA batteries, instruction manual and mounting sticker.

DigiFlow Electronic Flow Meter for use with a Body Glove Water Filter System.

A smarter way to change your cartridge! Flow Meter counts the gallons of filtered water used with a digital read, so you can change your cartridge at capacity. Alarm sounds when capacity has been reached.

- Filter capacity life monitor up to 19,900 gallons Filter elapse time monitor, up to 720 days •
- Flow rate display = 0.25–3.5 GPM
 Near end of filter life alert
 End of filter life alert
 Low battery alert

TEMPERATURE: 32-176°F / PRESSURE: max. 80 psi / WEIGHT: 5.38 oz / Connection: 3/8" NPT female



TDS TESTER



Part # WI-ENV-TDS-TESTER*

Shipping Wt: 1 lb.

\$77

Dimensions: Width: 1-1/16" Height: 6" Depth: 3/4"

- Total dissolved solids test meter Use to test the minerals in your water
- Test Reverse Osmosis membrane effectiveness.

WATER PRESSURE REGULATOR



Part # WI-PRESSURE-REGULATOR-60 Shipping Wt: 1 lb.

\$125

Undetected high water pressure is dangerous in any home.

For a margin of safety, we highly recommend the water pressure regulator for use with our Water, Inc. products.

Water Pressure Regulator installs in-line before water enters our products.

Dimensions: Length: 4" Circumference: 4.5" (fits 1/4" lines).

Maximum inlet pressure: 230 PSI

Maximum recommended water pressure for Water, Inc. products is 75 PSI. If you have pressure above 75 PSI, purchase this product.

*These products do not fall under no-lead legislation.