



Substance	Influent Challenge Concentration	Max. Permissible Product Water Concentration	Reduction Requirements	Average Reduction
<b>STANDARD 42</b>				
Chlorine Taste & Odor	2.0 mg/L $\pm$ 10%		>50%	95.9%
<b>STANDARD 53</b>				
Cysts*	Minimum 50,000/L		99.95%	99.99%
Atrazine	0.009 mg/L $\pm$ 10%	0.003 mg/L		93.7%
Lead (pH 6.5)	0.15 mg/L $\pm$ 10%	0.010 mg/L		99.9%
Lead (pH 8.5)	0.15 mg/L $\pm$ 10%	0.010 mg/L		99.6%
Lindane	0.002 mg/L $\pm$ 10%	0.0002 mg/L		97.4%
<b>STANDARD 58</b>				
Total Dissolved Solids	750 $\pm$ 40 mg/L	187 mg/L		96.3%
Pentavalent Arsenic	0.050 mg/L $\pm$ 10%	0.010 mg/L		88.0%
Fluoride	8.0 mg/L $\pm$ 10%	1.5 mg/L		93.6%
Cysts*	Minimum 50,000/mL		99.95%	99.99%
Turbidity	11 mg/L $\pm$ 1 NTU	0.5 NTU		>99.1%
Lead	0.15 mg/L $\pm$ 10%	0.010 mg/L		98.6%
Selenium	0.10 mg/L $\pm$ 10%	0.05 mg/L		97.9%
Copper	3.0 mg/L $\pm$ 10%	1.3 mg/L		98.5%
Cadmium	0.03 mg/L $\pm$ 10%	0.005 mg/L		99.1%
Hexavalent Chromium	0.3 mg/L $\pm$ 10%	0.1 mg/L		96.4%
Trivalent Chromium	0.3 mg/L $\pm$ 10%	0.1 mg/L		98.2%
Radium 226/228	25 pCi/L $\pm$ 10%	5 pCi/L		80.0%
Barium	10.0 mg/L $\pm$ 10%	2.0 mg/L		96.3%

### THE FINEST IN REVERSE OSMOSIS IS THE HP-RO-3000

- ✓ Truly purified.
- ✓ Designed to remove many impurities from your water.
- ✓ Provides 21 gallons of pure water per day for you and your family.
- ✓ The perfect choice for homes with water softeners.
- ✓ Click-in lock cartridge installation.
- ✓ Color coded cartridges maintains proper filter sequence.
- ✓ NSF certified for peace of mind (NSF Standard 42, 58 and 53).
- ✓ Designed for regions with specific water concerns like arsenic.
- ✓ Reduces Fluoride.
- ✓ A good choice if you are concerned about nitrates.
- ✓ Chrome air gap faucet included.
- ✓ TDS meter included to check your membrane performance annually.
- ✓ Ask about our upgrade products: we have decorative RO faucets and a multi-purpose air gap that are available in many finishes.

SYSTEM	PART NUMBER
HOUSEPURE REVERSE OSMOSIS	WI-HP-RO-3000

REPLACEMENT CARTRIDGES	PART NUMBER
3-CARTRIDGE KIT (change annually)	WI-HP-RO-3000-FILTER-KIT
MEMBRANE (change based on performance)	WI-HP-RO-3000-MEMBRANE

Change membrane based on performance: check TDS annually and change when reduction drops below 80%.

### SPECS & PERFORMANCE DATA:

FILTRATION	HOUSING DIMENSIONS	WEIGHT	TANK SIZE	PRESSURE RANGE	RECOVERY RATING	EFFICIENCY RATING	TDS REJECTION	PRODUCTION
4 STAGE	12.54" H x 14.57" W x 5.46" D	8.9 lbs	14.61" H 10.91" DIAMETER	40-100 psi	41.05%	23.57%	96.3%*	21.08 GPD

WARNING: For drinking water applications, do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. 1 year factory warranty.

\*NSF/ANSI Standard 53 & 58 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means.

# HOUSEPURE® REVERSE OSMOSIS HP-RO-3000



**Which type of filter is best for you?**

## CARBON BLOCK FILTRATION

LOWER MAINTENANCE,  
LOWER COST

SIMPLER  
INSTALLATION

BETTER FOR  
LIMITED SPACES

LEAVES NATURALLY  
FOUND MINERALS  
IN THE WATER

TARGETS SPECIFIC  
CONTAMINANTS LEAVING  
SAFE WATER

WATER WITH MINERALS  
HAS A PLEASANT TASTE



TRY A  
CARBON BLOCK  
**BODY GLOVE  
WATER FILTER  
SYSTEM**  
**BG-12000**

## REVERSE OSMOSIS FILTRATION

FOR REGIONS WITH SPECIFIC  
WATER CONCERNS (ARSENIC)

IF YOU WANT  
FLUORIDE REDUCTION

REQUIRES MORE  
UNDERSINK SPACE

REMOVAL OF  
VITAMINS & MINERALS

UTILIZES MULTI-STAGE  
PROCESS TO REMOVE AS  
MUCH AS POSSIBLE

WATER HAS NO TASTE,  
A BLANK SLATE TO ALLOW  
YOU TO TRULY TASTE  
FLAVOR OF BEVERAGES  
MADE WITH RO WATER



TRY THIS  
REVERSE OSMOSIS  
**HOUSEPURE  
WATER FILTER  
SYSTEM**  
**HP-RO-3000**

**14.57" WIDTH**  
**5.46" DEPTH**  
**12.54" OVERALL HEIGHT OF CARTRIDGE HOUSING**

**HIGH POWER MAGNET MOUNTED COVER**  
FOR EASE OF INSTALLATION

**UNIQUE DESIGN**  
EFFORTLESS CLICK-IN CARTRIDGE CHANGE

**BUILT-IN SHUTOFF VALVES**  
FOR EASY CARTRIDGE CHANGE

**COLOR CODED CARTRIDGES**  
MAINTAINS PROPER FILTER SEQUENCE

**3/8" PUSH FIT CONNECTIONS**  
EASY INSTALL & HIGH FLOW

**DOUBLE O-RING DESIGN**  
OPTIMAL CARTRIDGE SEALING

**REDUCES LEAD**

Chlorine Taste & Odor

Dissolved Solids

Cysts\*

Lindane

Atrazine

**WATER SUPPLY VALVE**  
SHUT OFF FOR EASE OF SERVICING  
FITS MULTIPLE PIPING STYLES

**TANK DIAMETER 10.91"**  
**14.61" TANK HEIGHT**

**TANK & CHROME FAUCET INCLUDED**  
PROVIDING YOU & YOUR FAMILY  
21 GALLONS PER DAY  
OF THE FINEST WATER

## WHOLE HOUSE WATER TREATMENT SYSTEMS

Our family of water treatment systems for your family:



### HP-SECURE

tankless water heater protection



### HP-CLASSIC

whole home/no power, no drain



### HP-02

whole home water filter



### HP-SCALESTOP

salt-free conditioner & filter



### HP-SOFT

traditional softener

\*NSF/ANSI Standard 53 & 58 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means.



800-322-WATER(9283) / WATERINC.COM